

## Section 1 Identification of Chemical Product and Company

Code	Description	Size	Colour
20155	Soudal Underbody Protective Coating Gun Grade	1Kg	Black

Recommended use:	Sealer		
HSNO Group Standard	HSR002662		
UN number, shipping name and packaging group:	UN1139	Coating Solution	PG II
Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80	
	14 Avalon Drive	Phone: (07) 847 5540	
	Nawton		
	Hamilton 3200	Email: info@soudal.co.nz	
	New Zealand	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>	
<b>POISON CENTRE NUMBER: 0800 764 766 (24 hours)</b>			

## Section 2 Hazards Identification

### Statement of Hazardous Nature

This product is classified as:

**HAZARDOUS SUBSTANCE** according to the criteria of HSNO.

**REGULATED** under NZS5433:2020 Transport of Dangerous Goods on Land

### Hazardous Substances and New Organisms (HSNO) classification:

Classification	GHS Hazard statements
<b>Flammable Liquid Category 2</b>	H225 Highly flammable liquid and vapour
<b>Eye Effects Category 2</b>	H318 Causes serious eye irritation
<b>STOT – SE NE Category 3</b>	H336 May cause drowsiness or dizziness
<b>Aspiration Category 1</b>	H304 May be fatal if swallowed and enters airways
<b>Chronic Aquatic Hazard Category 2</b>	H411 Toxic to aquatic life with long lasting effects

HSNO Signal Word:

**DANGER**



### Precautionary Statements:

Keep out of reach of children

Ensure all safety directions are read and understood before use

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P240 Ground and bond container and receiving equipment
- P241 Use explosion proof electrical/ ventilating/ lighting/ intrinsically safe equipment
- P242 Use only non-sparking tools
- P243 Take action against static discharges
- P261 Avoid breathing fumes/ mists/ vapours/ sprays

- P271 Use only in a well-ventilated area
- P280 Wear protective gloves, protective clothing, eye protection and face protection
- P264 Wash all exposed external body areas thoroughly after handling
- P370+378 In case of fire use alcohol resistant foam or normal protein foam to extinguish
- P273 Avoid release to the environment
- P391 Collect spillage

P403+235 Store in a well-ventilated place. Keep cool  
 P405 Store locked up

P501 Dispose of contents/ container to authorised hazardous or special waste collection point in accordance with any local regulation

### Section 3. Composition/Information on Ingredients

Ingredient	CAS No.	Individual HSNO classification	Concentration (% by Wt.)
Hydrocarbons, C <sub>7-9</sub> n-alkanes, isoalkanes, cyclics	64742-49-0	Flammable Liquid Category 2; STOT – SE NE Category 3; Aspiration Category 1; Chronic Aquatic Hazard Category 2	25 – 50 %
Propylene carbonate	108-32-7	Eye Effects Category 2	1 – 5 %
Hydrocarbons, C <sub>9</sub> aromatics	64742-95-6	Flammable Liquid Category 3; Acute Dermal Toxicity Category 4; STOT – SE NE Category 3; Aspiration Category 1; Chronic Aquatic Hazard Category 3	1 – 5 %
Ingredients not contributing to the classification			balance

### Section 4 First Aid Measures<sup>74</sup>

**NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111**

**Eye contact:**

Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

**Skin contact:**

Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation

**Inhalation:**

remove from contaminated area. Other measures are usually unnecessary

**Ingestion:**

Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

**General advice and advice for physicians:**

Treat symptomatically.

### Section 5 Fire-Fighting Measures

**Extinguishing media:**

Foam; Water spray, dry chemical or CO<sub>2</sub>

**Fire Incompatibility:**

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

**Special hazards due to combustion:**

Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO).

**Advice for fire-fighters:**

Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.

### Section 6 Accidental Release Measures

**Minor Spills**

Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up. Collect residues in a flammable waste container.

**Major Spills**

Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Equipment should be thoroughly decontaminated after use.

**Section 7 Handling and Storage**

**Handling:**

Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Electrostatic discharge may be generated during pumping - this may result in fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec). Avoid splash filling. Do NOT use compressed air for filling discharging or handling operations. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights, heat or ignition sources. When handling, DO NOT eat, drink or smoke. Vapour may ignite on pumping or pouring due to static electricity. DO NOT use plastic buckets. Earth and secure metal containers when dispensing or pouring product. Use spark-free tools when handling. Avoid contact with incompatible materials. Keep containers securely sealed. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

**Storage:**

Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. Keep containers securely sealed. Store away from incompatible materials in a cool, dry well-ventilated area. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

**Suitable Container:**

Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.

**Section 8 Exposure Controls/Personal Protection**

**Exposure Limits**



CAS no.	Substance or ingredient	WES-TWA	WES-STEL


The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

**Engineering Controls:**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

**Exposure controls:**

Control	Protective measure
Eye	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [AS/NZS 1336 or national equivalent] Close fitting gas tight goggles 
Respiratory	Not normally required. Where inadequate ventilation exists then a Type A filter is recommended 

<b>Skin</b>	Nitrile+PVC gloves. Avoid skin contact. If skin contact or contamination of clothing is likely, protective clothing should be worn. [AS 2161] Wear protective clothing.	
-------------	---	---

## Section 9 Physical and Chemical Properties

### General substance properties:

Property	Details
<b>Appearance</b>	Black liquid
<b>Odour</b>	Characteristic
<b>pH</b>	No data
<b>Vapour pressure</b>	11.1 kPa
<b>Viscosity</b>	No data
<b>Vapour Density</b>	No data
<b>Boiling Point</b>	106 – 140 °C
<b>Volatile materials</b>	No data %
<b>Freezing/melting point</b>	No data
<b>Solubility</b>	No data
<b>Specific gravity/density</b>	1.09 g/ml
<b>Flash point</b>	6 °C
<b>Danger of explosion</b>	Not applicable
<b>Auto-ignition temperature</b>	200 °C
<b>Upper and lower flammability limits</b>	LEL 0.9 % UEL 7.0 %
<b>Evaporation Rate</b>	No data Butyl acetate = 1
<b>Corrosiveness</b>	No data
<b>Viscosity</b>	>20.5 mm <sup>2</sup> /s 40°C

## Section 10 Stability and Reactivity

### Stability:

Stable under normal conditions.

### Conditions to avoid:

Exposure to excessive heat, open flames and sparks. Avoid conditions that favour the formation of excessive mists and/or fumes. Contact with water may release flammable gases.

### Incompatible materials to avoid:

Avoid oxidising agents, strong acids and strong bases.

### Hazardous decomposition products:

Combustion will result in the release of carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>); and pyrolysis products typical of burning organic material. May emit corrosive fumes.

## Section 11 Toxicological Information

Test	Data and symptoms of exposure
<b>Inhaled</b>	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. There may be a reduction red blood cells and bleeding abnormalities. There may also be drowsiness. Symptoms are temporary, and include weakness, tremors, increased saliva, some convulsions, excessive tears with discolouration and inco-ordination lasting up to 24 hours. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Heart stoppage may result from cardiovascular collapse. A slow heart rate and low blood pressure may also occur.
<b>Oral</b>	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Chronic inhalation or skin exposure to n-hexane may cause damage to nerve ends in extremities, e.g. finger, toes with loss of sensation
<b>Dermal</b>	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Rare sensitisation reactions in humans have occurred. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the bloodstream through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. The material may accentuate any pre-existing dermatitis condition
<b>Eye</b>	This material can cause eye irritation and damage in some persons
<b>Chronic</b>	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless, exposure by all routes should be minimised as a matter of course. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

	Oral LD <sub>50</sub> mg/m <sup>3</sup>	Dermal LD <sub>50</sub> mg/m <sup>3</sup>	Inhalation LC <sub>50</sub> mg/L
Hydrocarbons, C <sub>7-9</sub> n-alkanes, isoalkanes, cyclics	>5840	>2920	>23.3 /4h
Propylene carbonate	>5000	>2000	
Hydrocarbons, C <sub>9</sub> aromatics	>4500	>1900	>4.42 /4h

## Section 12 Ecological Information

### Summary of Ecotoxicity

Toxic to aquatic life with long lasting effects. Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high-water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites. DO NOT discharge into sewer or waterways.

	Fish mg/L	Crustacea mg/L	Algae mg/L
Hydrocarbons, C <sub>7-9</sub> n-alkanes, isoalkanes, cyclics	LC <sub>50</sub> 96hr 4.26	EC <sub>50</sub> 48hr 0.64 NOEC 504hr 0.17	EC <sub>50</sub> 96hr 64
Propylene carbonate	LC <sub>50</sub> 96hr >1000	EC <sub>50</sub> 48hr >1000	EC <sub>50</sub> 72hr >900
Hydrocarbons, C <sub>9</sub> aromatics		EC <sub>50</sub> 48hr 6.14	EC <sub>50</sub> 72hr 19 EC <sub>50</sub> 96hr 64 NOEC 72hr 1

	Persistence H <sub>2</sub> O/ Soil	Persistence Air	Bioaccumulation	Mobility
Propylene Carbonate	HIGH	HIGH	LOW	LOW

## Section 13 Disposal Considerations

### Disposal methods:

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled. The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance. Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. DO NOT deposit the hazardous substance into or onto a landfill or a sewage facility. Burning the hazardous substance must happen under controlled conditions with no person or place exposed to (1) a blast overpressure of more than 9 kPa; or (2) an unsafe level of heat radiation. The disposed hazardous substance must not come into contact with class 1 or 5 substances.

## Section 14 Transport Information



HAZCHEM **3YE**

### Land Transport UNDG

UN Number	<b>1139</b>
Shipping Name	<b>Coating solution</b>
Class or division	<b>3</b>
Subsidiary Risk	None
UN Packing Group	<b>II</b>
Environmental hazard	<b>Environmentally hazardous</b>
Special Provisions	not applicable
Limited Quantities	<b>5 L</b>

### Air Transport IATA

UN/ID Number	<b>1139</b>
Shipping Name	<b>Coating Solution</b>
ICAO/IATA Class	<b>3</b>
ICAO/IATA Subrisk	None
ERG Code	<b>3L</b>
Packing Group	<b>II</b>
Environmental hazard	<b>Environmentally hazardous</b>
Special provision	<b>A3</b>
Cargo only	
Packing instructions	<b>364</b>
Maximum Qty/pack	<b>60 L</b>
Passenger and Cargo	
Packing instructions	<b>353</b>
Maximum Qty/pack	<b>5 L</b>
Passenger & Cargo Limited Quantity	
Packing instructions	<b>Y341</b>
Maximum Qty/pack	<b>1 L</b>

### Marine Transport IMDG

UN Number	<b>1139</b>
Shipping Name	<b>Coating Solution</b>
IMDG Class	<b>3</b>
IMDG Subrisk	None
UN Packing Group	<b>II</b>
Environmental hazard	<b>Marine Pollutant</b>
EmS Number	<b>F-E, S-E</b>

Special provisions            None  
 Limited quantities            5 L

## Section 15 Regulatory Information

### HSNO approval number and Group Standard:

HSR002662            Surface Coatings & Colourants Flammable

### Group Standard conditions and other regulations:

Condition	Requirement
SDS	Safety data sheet must be available to a person handling the substance within 10 minutes.
Emergency plan	Required when present in quantities exceed 100 Lt.
Certified Handler	Not required
Tracking	Not required
Bundling and secondary containment	Based on total volumes and pack sizes held on site
Signage	Required when present in quantities exceed 100 Lt
Location Compliance certificate	Flammable Liquid Category 2 when quantities exceed 100L in closed containers of more than 5 Lt capacity, and/or greater than 250L in closed container of less than 5 Lt capacity and/or greater tha 50Lt in open container
Hazardous Atmosphere Zone	Required to meet the requirements of AS/NZS 60079.10
Fire extinguisher	2 required when quantities exceed 250 Lt

### National Inventories

*Y = All ingredients are on the inventory*

Australia	AICS	Y
Canada	DSL	Y
Canada	NDSL	N
China	IECSC	Y
Europe	EINEC/ELINCS/NLP	Y
Japan	ENCS	N
Korea	KECI	Y
New Zealand	NZIOC	Y
Philippines	PICCS	Y
USA	TSCA	Y
Taiwan	TCSI	Y
Mexico	INSQ	Y
Vietnam	NCI	Y
Russia	ARIPS	Y
Thailand	TECI	Y

## Section 16 Other Information

### Revision History:

October 2021            Review and update to GHS v7 format  
 July 2019                Error correction plus additional disposal information  
 June 2017                Initial preparation

### Abbreviations:

Abbreviation	Description
CAS number	Number assigned to chemical in the Chemical Abstracts Service registry
HAZCHEM code	Code used by fire-fighters to determine correct method of action in the case of fire
HSNO	Hazardous Substances and New Organisms (Act)



ICAO Technical Instructions	International Civil Aviation Organization Technical Instructions
IMDG code	International Maritime Dangerous Goods code controlled by the International Maritime Organization (IMO)
LC <sub>50</sub>	Lethal concentration 50% - concentration fatal to 50% of the tested population
LD <sub>50</sub>	Lethal dose 50% - dose fatal to 50% of the tested population
NZS 5433	New Zealand Standard 5433 (Standard for the Transport of Dangerous Goods on Land)
SDS	Safety data sheet
STEL	Short term exposure limit
TWA	Time weighted average (typically measured as 8 hours)
UN number	United nations number
WES	Workplace exposure standard

#### References

Chemical properties and HSNO classifications derived from the New Zealand chemical classification information database (CCID). [www.epa.govt.nz](http://www.epa.govt.nz)  
 Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 12-1 Edition.

***The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other material or in any process, unless specified in the text.***

This SDS was prepared by Collievale Enterprises Ltd in accord with the Hazardous Substances (Safety Data Sheets) Notice 2017  
<http://www.collievale.com> Phone +64 7 5432428

End of SDS