

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: SabreSeal Duct Sealant
Product Use: Sealant
Restrictions of use: Refer to Section 15

New Zealand Supplier: Sabre Adhesives Ltd
Address: 42 Cambridge Street South
Levin, 5510, New Zealand
Telephone: +64 (0)6 366 0007
Emergency No: **0800 764 766 (National Poison Centre)**

Australian Supplier: Sabre Adhesives Ltd
Address: Level 6, 10 Herb Elliot Avenue, Sydney NSW, 2127
Telephone No: +61 2 9098 8244
Emergency No: **13 11 26 (National Poison Line)**

Date SDS Issued: 24 July 2023

Section 2. Hazards Identification

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

Classified as hazardous according to Regulation (EC) No. 1272/2008 [CLP] which meets New Zealand jurisdiction criteria as per EPA Hazardous Substances (Safety Data Sheets) Notice 2017 Part B Clause 9.

NZ - EPA Approval Code: Surface Coatings and Colourants (Flammable) - HSR002662

Pictograms



Signal Word: DANGER

GHS Category	Hazard Code	Hazard Statement
Flammable Liquids Cat. 2	H225	Highly flammable liquid and vapour.
Skin irritation Cat. 2	H315	Causes skin irritation.
Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Reproductive toxicity Cat. 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity -	H373	May cause damage to organs through prolonged

repeated exposure Cat. 2		or repeated exposure.
specific target organ toxicity - single exposure Cat 3 - Narcotic Effects	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment chronic Cat. 3	H412	Harmful to aquatic life with long lasting effects.

Prevention Code Prevention Statement

P103	Read carefully and follow all instructions.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical, ventilating and lighting] equipment
P242	Use non-sparking tools.
P243	Take action to prevent static discharge.
P260	Do not breathe dust, fumes, gas, mist, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

Response Code Response Statement

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash it before reuse.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use ... <specify appropriate media> to extinguish. - This statement applies if water increases risk.

Storage Code Storage Statement

P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code Disposal Statement

P501	Dispose of according to the local authorities
------	---

Section 3. Composition of hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Toluene	30 - 60	108-88-3
P-Tert-Butylphenol-Formaldehyde Resin	1 - 10	25085-50-1
Zinc Oxide	0.1 - 1	1314-13-2
rosin; colophony	0.1 - 1	8050-09-7
Amide Wax	0.1 - 1	Proprietary

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice.
If on Skin	Take off contaminated clothing and wash before re-use. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
If Swallowed	Rinse mouth with water. Never give anything by mouth to an unconscious person. Seek medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:	Not applicable.
Inhalation:	May cause drowsiness or dizziness.
Skin:	Causes skin irritation. May cause an allergic skin reaction.
Eye:	Not applicable.
Chronic:	May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

Notes to Doctor: Treat symptomatically.

Section 5. Fire Fighting Measures

Hazard Type	Highly flammable liquid and vapour.
Hazards from products	Toxic fumes may be released.
Suitable Extinguishing media	Dry powder. Foam. Carbon dioxide. Do not use water spray.
Precautions for firefighters and special protective clothing	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
HAZCHEM CODE	3YE

Section 6. Accidental Release Measures

For emergency responders:

Do not attempt to take action without suitable protective equipment as detailed in Section 8. Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe fumes, vapours or spray. Avoid contact with skin and eyes.

Environmental precautions:

Avoid release to the environment.

Methods and material for containment and cleaning up:

Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters. Dispose as per Section 13.

Section 7. Handling and Storage

Precautions for Handling:

- Read carefully and follow all instructions.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Ground and bond container and receiving equipment.
- Use explosion-proof [electrical, ventilating and lighting] equipment
- Use non-sparking tools.
- Take action to prevent static discharge.
- Do not breathe fumes, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Avoid contact with skin and eyes.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.
- Use personal protective equipment as required.

Precautions for Storage:

- Store locked up.
- Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Store away from incompatible materials listed in Section 10.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Toluene (Toluol)	[108-88-3]	20	75	100	377
Zinc oxide	[1314-13-2]	-	2	-	5

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

Ensure good ventilation of the work station.

Personal Protection Equipment



Eyes	Safety glasses.
Hands	Wear protective gloves.

Skin	Wear suitable protective clothing.
Respiratory	In case of inadequate ventilation wear respiratory protection.

Section 9 Physical and Chemical Properties
--

Appearance	Liquid
Colour	Grey
Odour	Aromatic
Odour Threshold	Not available
pH	Not available
Boiling Point	>56°C
Melting/Freezing Point	Not available
Flash Point	<23°C
Flammability	Highly Flammable liquid or vapour
Upper and Lower Explosive Limits	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Relative Density	~1.30
Solubility in water	Not available
Partition Coefficient:	Not available
Auto-ignition Temperature	Not available
VOC g/L	Not available
Particle Characteristics	Not available
Viscosity, dynamic	1600000-1850000 cP
Viscosity, kinematic	>40 mm ² /s

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
Conditions to Avoid	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible Materials	No additional information available.
Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 Toxicological Information
--

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	May cause drowsiness or dizziness.
Eye	Not applicable.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.

Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	May cause damage to organs through prolonged or repeated exposure.

toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Section 12. Ecotoxicological Information

Harmful to aquatic life with long lasting effects.

Persistence and degradability	No additional information available
Biodegradation	No additional information available
Bioaccumulative potential	No additional information available
Mobility in soil	No additional information available
Effects in sewage plants:	No additional information available
Other adverse effects	No additional information available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – Flammable, Ecotoxic" and that the label also has the Flammable, Ecotoxic Pictogram, waste type identifier, and the business name, address, and phone number.

Precautions or methods to avoid: Avoid release to the environment.

Section 14 Transport Information

**This product is classified as a Dangerous Good for transport in Australia; ADG 7
This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2020
and SNZ HB 5433:2021**



Road, Rail, Sea and Air Transport

UN No	1133
Class - Primary	3
Packing Group	II
Proper Shipping Name	ADHESIVES (containing flammable liquid)

Product Name: SabreSeal Duct Sealant
Date of SDS: 24 July 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: +64 9 475 5240 WWW.techcomp.co.nz

Marine Pollutant	No
Special Provisions	If the product's individual container is below 5L it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15 Regulatory Information

Australia:

Australia NOHSC – Hazardous according to Safe Work Australia NOHSC 2011 National Code of Practice

Poison Schedule No: Schedule 6

New Zealand:

Classified as hazardous according to Regulation (EC) No. 1272/2008 [CLP] which meets New Zealand jurisdiction criteria as per EPA Hazardous Substances (Safety Data Sheets) Notice 2020.

NZ - EPA Approval Code: Surface Coatings and Colourants (Flammable) - HSR002662

Trigger quantities for this substance:

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	100L (>5L), 250L (<5L), 50L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250L
Emergency Response Plan	1000L
Secondary Containment	1000L
Fire Extinghiser	250 L = 2x
Restriction of Use	Only use for the intended purpose.

Section 16 Other Information

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.

Product Name: SabreSeal Duct Sealant
Date of SDS: 24 July 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: +64 9 475 5240 WWW.techcomp.co.nz

4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).
7. Globally Harmonised System of classification and labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13th edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 24 July 2023

Review Date: 24 July 2028